

Technical data sheet

227C-024-15

Continuous control rotary drive without spring return

Description

Actuator for adjusting air dampers of 90° angle of rotation to be used in HVAC installations.

- Torque Motor 15 Nm
- Nominal Voltage 24 VAC/DC
- Control Continuous control DC
0(2)...10 V
- Damper size up to approx. 3 m²
- Damper coupling Clamp
∅ 8-12 mm / Ø 8-16 mm



Technical data

Nominal voltage	Nominal voltage	24 VAC/DC
	Nominal voltage range	19...29 VAC/DC
	Power consumption Motor (Motion)	2 W
	Power consumption Standby (end position)	1 W
	Wire sizing	3,5 VA
	Control	Continuous control 0(2)...10 VDC / Ri >100 kΩ 0(4)...20 mA / Rext.=500Ω
	Position feedback	0(2)...10 VDC, max 5 mA
	Auxiliary switch	-
	Contact load	-
	Switching point	-
	Connection Motor	Cable 1000 mm, 4 x 0,75 mm ² (halogen free)
	Connection Auxiliary switch	-
	Connection Position feedback	-
	Connection GUAC	-
Functional data	Torque Motor	>15 Nm
	Synchronised speed	±5%
	Direction of rotation	selected by switch
	Manual override	Gearing latch disengaged with pushbutton, self-resetting
	Angle of rotation	0°... max. 95°, can be limited with adjustable mechanical end stop
	Running time Motor	< 150 s / 90°
	Sound power level Motor	< 35 dB(A)
Damper coupling	Clamp ∅ 8-12 mm / Ø 8-16 mm	

Technical data

Functional data	Position indication	mechanical with pointer
	Service life	>60'000 cycles (0° - 95° - 0°)
Safety	Protection class	III (low voltage safety current)
	Degree of protection	IP54 (Cable downwards)
	CE	73/23 EWG, 89/336 EWG
	Mode of operation	Typ 1 (EN 60730-1)
	Rated impulse voltage	0,8 kV (EN 60730-1)
	Control pollution degree	3 (EN 60730-1)
	Ambient temperature Normal operation	-30°C...+50°C
	Storage temperature	-30°C...+80°C
	Ambient humidity	5...95% r.F., non- condensating (EN 60730-1)
	Maintenance	maintenance free
Dimensions/ Weight	Dimensions	115 x 65 x 61 mm
	Weight	ca. 530 g

Operating mode / Properties

Operating mode

Through connecting the power supply to BU+BN (1+2) and a reference signal Y to BK (3) of 0(2)...10VDC, moves the actuator to its specified position. The actual damper position 0...100% is a feedback signal U for example to share the signal with other actuators.

The actuator is overload-proof, requires no limit switches and automatically stops when the end stop is reached.

Direct mounting

Simple direct mounting on the damper spindle with a universal spindle clamp, supplied with an anti-rotation strap to prevent the actuator from rotating.


Manual override

Manual override is possible with the self-resetting pushbutton (the gearing latch remains disengaged as long as the pushbutton is pressed)


Mode- switch

Mode- switch with five positions at the housing

- Rotary direction right 2-10 V
- Rotary direction right 0-10 V
- Adp = Adaption
- Rotary direction left 0-10 V
- Rotary direction left 2-10 V



Connection / Safety remarks


Safety remarks

- Connect via safety isolation transformer
- The actuator is not allowed to be used outside the specified field of application, especially in airplanes.
- In may only be installed by suitably trained personnel. Any legal regulations or regulations issued by authorities must be observed during assembly.
- The device may only be opened at the manufacturer's site.
- When calculating the required torque, the specifications supplied by the damper manufacturers (cross- section, design, installation site), and the air flow conditions must be observed.
- The actuator is not allowed to be disposed of as household refuse. All locally valid regulations and requirements must be observed.

Technical drawing

